

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C11D 17/00	A1	(11) International Publication Number: WO 98/00518 (43) International Publication Date: 8 January 1998 (08.01.98)
(21) International Application Number: PCT/US97/10790 (22) International Filing Date: 26 June 1997 (26.06.97) (30) Priority Data: 60/020,999 28 June 1996 (28.06.96) US (71) Applicant (for all designated States except US): THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): SMERZNAK, Mark, Allen [US/US]; 4039 Taylor Avenue, Cincinnati, OH 45209 (US). PARRY, Diane [US/US]; 9568 Brehm Road, Cincinnati, OH 45252 (US). KAHN, Jay, Ian [US/US]; 3645 Burch Avenue, Cincinnati, OH 45208 (US). (74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).		(81) Designated States: BR, CA, CN, JP, MX, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: PREPARATION OF NON-AQUEOUS, PARTICULATE-CONTAINING LIQUID DETERGENT COMPOSITIONS WITH PREPROCESSED DRIED COMPONENTS (57) Abstract Disclosed is a process for preparing non-aqueous, particulate-containing liquid laundry detergent compositions which are in the form of a suspension of particulate material, preferably including anionic surfactant, peroxygen bleaching agent and an organic detergent builder, dispersed in a liquid phase, preferably structured with the anionic surfactant. Such compositions provide especially desirable cleaning and bleaching of fabrics laundered therewith and also exhibit especially desirable pourability and chemical and phase stability. The process for preparing such compositions involves preprocessing of the particulate material to remove free moisture from the hydrated or hydratable particulate components of the composition.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**PREPARATION OF
NON-AQUEOUS, PARTICULATE-CONTAINING
LIQUID DETERGENT COMPOSITIONS WITH
PREPROCESSED DRIED COMPONENTS**

FIELD OF THE INVENTION

This invention relates to preparation of liquid laundry detergent products which are non-aqueous in nature and which are in the form of stable dispersions of particulate material such as bleaching agents and/or other detergent composition adjuvants.

BACKGROUND OF THE INVENTION

Liquid detergent products are often considered to be more convenient to use than are dry powdered or particulate detergent products. Liquid detergents have therefore found substantial favor with consumers. Such liquid detergent products are readily measurable, speedily dissolved in the wash water, capable of being easily applied in concentrated solutions or dispersions to soiled areas on garments to be laundered and are non-dusting. They also usually occupy less storage space than granular products. Additionally, liquid detergents may have incorporated in their formulations materials which could not withstand drying operations without deterioration, which operations are often employed in the manufacture of particulate or granular detergent products.

Although liquid detergents have a number of advantages over granular detergent products, they also inherently possess several disadvantages. In particular, detergent composition components which may be compatible with each other in granular products may tend to interact or react with each other in a liquid, and especially in an aqueous liquid, environment. Thus such components as enzymes, surfactants, perfumes, brighteners, solvents and especially bleaches and bleach

activators can be especially difficult to incorporate into liquid detergent products which have an acceptable degree of chemical stability.

40 One approach for enhancing the chemical compatibility of detergent composition components in liquid detergent products has been to formulate non-aqueous (or anhydrous) liquid detergent compositions. In such non-aqueous products, at least some of the normally solid detergent composition components tend to remain insoluble in the liquid product and hence are less reactive with each other
45 than if they had been dissolved in the liquid matrix. Non-aqueous liquid detergent compositions, including those which contain reactive materials such as peroxygen bleaching agents, have been disclosed for example, in Hepworth et al., U.S. Patent 4,615,820, Issued October 17, 1986; Schultz et al., U.S. Patent 4,929,380, Issued May 29, 1990; Schultz et al., U.S. Patent 5,008,031, Issued April 16, 1991; Elder et al., EP-A-030,096, Published June 10, 1981; Hall et al., WO 92/09678, Published
50 June 11, 1992 and Sanderson et al., EP-A-565,017, Published October 13, 1993.

Even though chemical compatibility of components may be enhanced in non-aqueous liquid detergent compositions, physical stability of such compositions may become a problem. This is because there is a tendency for such products to phase
55 separate as dispersed insoluble solid particulate material drops from suspension and settles at the bottom of the container holding the liquid detergent product. As one consequence of this type of problem, there can also be difficulties associated with incorporating enough of the right types and amounts of surfactant materials into non-aqueous liquid detergent products. Surfactant materials must, of course, be selected
60 such that they are suitable for imparting acceptable fabric cleaning performance to such compositions but utilization of such materials must not lead to an unacceptable degree of composition phase separation. Phase stabilizers such as thickeners or viscosity control agents can be added to such products to enhance the physical stability thereof. Such materials, however, can add cost and bulk to the product
65 without contributing to the laundering/cleaning performance of such detergent compositions.

It is also possible to select surfactant systems for such liquid laundry detergent products which can actually impart a structure to the liquid phase of the product and thereby promote suspension of particulate components dispersed within such a
70 structured liquid phase. An example of such a product with a structured surfactant system is found in van der Hoeven et al.; U.S. Patent 5,389,284; Issued February 14, 1995, which utilizes a structured surfactant system based on relatively high concentrations of alcohol alkoxylate nonionic surfactants and anionic defloculating agents. In products which employ a structured surfactant system, the structured

75 liquid phase must be viscous enough to prevent settling and phase separation of the suspended particulate material, but not so viscous that the pourability and dispensability of the detergent product is adversely affected.

Given the foregoing, there is clearly a continuing need to identify and provide processes for preparing liquid, particulate-containing detergent compositions in the form of non-aqueous liquid products that have a high degree of chemical, e.g.,
80 bleach and enzyme, stability along with commercially acceptable phase stability, pourability and detergent composition laundering, cleaning or bleaching performance. Accordingly, it is an object of the present invention to provide a process for preparing non-aqueous, particulate-containing liquid detergent products
85 which have such especially desirable chemical and physical stability characteristics as well as outstanding pourability and fabric laundering/bleaching performance characteristics.

90

SUMMARY OF THE INVENTION

The present invention relates to a process for preparing non-aqueous liquid detergent compositions in the form of a stable suspension of solid, substantially insoluble particulate material dispersed throughout a non-aqueous liquid phase that
95 is preferably surfactant-containing and structured. Such a process comprises the steps of

A) forming a liquid base comprising one or more non-aqueous liquid organic diluents;

B) providing, for eventual combination with this liquid base, one or
100 more types of hydrated or hydratable particulate components which have an initial free, unbound moisture content of about 0.5% by weight or greater;

C) drying these hydrated or hydratable particulate components using a fluidized bed drying procedure to thereby reduce the free, unbound moisture content of the particulate components to a level of less than about 0.5% by weight; and
105 immediately thereafter

D) combining the dried hydrated or hydratable particulate components with the liquid base,

to thereby form the desired non-aqueous liquid detergent compositions.

110 The particulate components which are dried in this manner are selected from anionic surfactants, peroxygen bleaching agents, bleach activators, organic detergent builders and inorganic alkalinity sources. The particulate components range in particle size from about 0.1 to 1500 microns.

DETAILED DESCRIPTION OF THE INVENTION

115

The non-aqueous liquid detergent compositions prepared in accordance with the process of this invention comprise a non-aqueous, liquid phase, that is preferably structured and surfactant-containing, in which solid substantially insoluble particulate material is suspended. The components of the preferred structured liquid phase and the solid dispersed materials of the preferred detergent compositions prepared herein, as well as composition form, preparation steps and composition use, are described in greater detail as follows: (All concentrations and ratios are on a weight basis unless otherwise specified.)

125 SURFACTANT-STRUCTURED LIQUID PHASE

A surfactant-containing, structured liquid phase of the compositions prepared herein will generally comprise from about 45% to 95% by weight of the detergent compositions prepared herein. More preferably, this liquid phase will comprise from about 50% to 95% by weight of the compositions. Most preferably, this liquid phase will comprise from about 50% to 70% by weight of the compositions prepared herein. The structured liquid phase of the detergent compositions prepared herein is generally formed from one or more non-aqueous organic diluents into which is mixed a surfactant structuring agent which is preferably a specific type of anionic surfactant-containing powder.

135

(A) Non-aqueous Organic Diluents

The major component of the structured liquid phase of the preferred detergent compositions prepared herein comprises one or more non-aqueous organic diluents. The non-aqueous organic diluents used in this invention may be either surface active, i.e., surfactant, liquids or non-aqueous, non-surfactant liquids referred to herein as non-aqueous solvents. The term "solvent" is used herein to connote the non-aqueous liquid portion of the compositions prepared herein. While some of the essential and/or optional components of the compositions prepared herein may actually dissolve in the "solvent"-containing liquid phase, other components will be present as particulate material dispersed within the "solvent"-containing liquid

145


phase. Thus the term "solvent" is not meant to require that the solvent material be capable of actually dissolving all of the detergent composition components added thereto.

The non-aqueous liquid diluent component will generally comprise from about 150 50% to 99%, more preferably from about 50% to 80%, most preferably from about 55% to 75%, of the structured, surfactant-containing liquid phase. Preferably the liquid phase of the compositions prepared herein will comprise both non-aqueous, liquid surfactants and non-surfactant non-aqueous solvents.

155 i) Non-aqueous Surfactant Liquids

Suitable types of non-aqueous surfactant liquids which can be used to form the structured liquid phase of the compositions prepared herein include the alkoxyated alcohols, ethylene oxide (EO)-propylene oxide (PO) block polymers, polyhydroxy fatty acid amides, alkylpolysaccharides, and the like. Such normally 160 liquid surfactants are those having an HLB ranging from 10 to 16. Most preferred of the surfactant liquids are the alcohol alkoxylate nonionic surfactants.

Alcohol alkoxylates are materials which correspond to the general formula:



wherein R^1 is a $C_8 - C_{16}$ alkyl group, m is from 2 to 4, and n ranges from about 2 to 12. Preferably R^1 is an alkyl group, which may be primary or secondary, that 165 contains from about 9 to 15 carbon atoms, more preferably from about 10 to 14 carbon atoms. Preferably also the alkoxyated fatty alcohols will be ethoxylated materials that contain from about 2 to 12 ethylene oxide moieties per molecule, more preferably from about 3 to 10 ethylene oxide moieties per molecule.

170 The alkoxyated fatty alcohol materials useful in the liquid phase will frequently have a hydrophilic-lipophilic balance (HLB) which ranges from about 3 to 17. More preferably, the HLB of this material will range from about 6 to 15, most preferably from about 8 to 15.

Examples of fatty alcohol alkoxylates useful in or as the non-aqueous liquid 175 phase of the compositions prepared herein will include those which are made from alcohols of 12 to 15 carbon atoms and which contain about 7 moles of ethylene oxide. Such materials have been commercially marketed under the trade names Neodol 25-7 and Neodol 23-6.5 by Shell Chemical Company. Other useful Neodols include Neodol 1-5, an ethoxylated fatty alcohol averaging 11 carbon atoms in its 180 alkyl chain with about 5 moles of ethylene oxide; Neodol 23-9, an ethoxylated primary $C_{12} - C_{13}$ alcohol having about 9 moles of ethylene oxide and Neodol 91-10, an ethoxylated $C_9 - C_{11}$ primary alcohol having about 10 moles of ethylene

oxide. Alcohol ethoxylates of this type have also been marketed by Shell Chemical Company under the Dobanol tradename. Dobanol 91-5 is an ethoxylated C₉-C₁₁ fatty alcohol with an average of 5 moles ethylene oxide and Dobanol 25-7 is an ethoxylated C₁₂-C₁₅ fatty alcohol with an average of 7 moles of ethylene oxide per mole of fatty alcohol.

Other examples of suitable ethoxylated alcohols include Tergitol 15-S-7 and Tergitol 15-S-9 both of which are linear secondary alcohol ethoxylates that have been commercially marketed by Union Carbide Corporation. The former is a mixed ethoxylation product of C₁₁ to C₁₅ linear secondary alkanol with 7 moles of ethylene oxide and the latter is a similar product but with 9 moles of ethylene oxide being reacted.


Other types of alcohol ethoxylates useful in the presently prepared compositions are higher molecular weight nonionics, such as Neodol 45-11, which are similar ethylene oxide condensation products of higher fatty alcohols, with the higher fatty alcohol being of 14-15 carbon atoms and the number of ethylene oxide groups per mole being about 11. Such products have also been commercially marketed by Shell Chemical Company.

If alcohol alkoxylate nonionic surfactant is utilized as part of the non-aqueous liquid phase in the detergent compositions prepared herein, it will preferably be present to the extent of from about 1% to 60% of the composition structured liquid phase. More preferably, the alcohol alkoxylate component will comprise about 5% to 40% of the structured liquid phase. Most preferably, an alcohol alkoxylate component will comprise from about 5% to 35% of the detergent composition structured liquid phase. Utilization of alcohol alkoxylate in these concentrations in the liquid phase corresponds to an alcohol alkoxylate concentration in the total composition of from about 1% to 60% by weight, more preferably from about 2% to 40% by weight, and most preferably from about 10% to 25% by weight, of the composition.

Another type of non-aqueous surfactant liquid which may be utilized in this invention are the ethylene oxide (EO) - propylene oxide (PO) block polymers. Materials of this type are well known nonionic surfactants which have been marketed under the tradename Pluronic. These materials are formed by adding blocks of ethylene oxide moieties to the ends of polypropylene glycol chains to adjust the surface active properties of the resulting block polymers. EO-PO block polymer nonionics of this type are described in greater detail in Davidsohn and Milwidsky; Synthetic Detergents, 7th Ed.; Longman Scientific and Technical (1987) at pp. 34-36 and pp. 189-191 and in U.S. Patents 2,674,619 and 2,677,700. All of

220 these publications are incorporated herein by reference. These Pluronic type nonionic surfactants are also believed to function as effective suspending agents for the particulate material which is dispersed in the liquid phase of the detergent compositions prepared herein.

225 Another possible type of non-aqueous surfactant liquid useful in the compositions prepared herein comprises polyhydroxy fatty acid amide surfactants. Materials of this type of nonionic surfactant are those which conform to the formula:



wherein R is a C₉₋₁₇ alkyl or alkenyl, p is from 1 to 6, and Z is glycityl derived from a reduced sugar or alkoxyated derivative thereof. Such materials include the
 230 C₁₂-C₁₈ N-methyl glucamides. Examples are N-methyl N-1-deoxyglucityl cocoamide and N-methyl N-1-deoxyglucityl oleamide. Processes for making polyhydroxy fatty acid, amides are known and can be found, for example, in Wilson, U.S. Patent 2,965,576 and Schwartz, U.S. Patent 2,703,798, the disclosures of which are incorporated herein by reference. The materials themselves and their preparation
 235 are also described in greater detail in Honsa, U.S. Patent 5,174,937, Issued December 26, 1992, which patent is also incorporated herein by reference.

The amount of total liquid surfactant in the preferred surfactant-structured, non-aqueous liquid phase herein will be determined by the type and amounts of other composition components and by the desired composition properties.
 240 Generally, the liquid surfactant can comprise from about 35% to 70% of the non-aqueous structured liquid phase of the compositions prepared herein. More preferably, the liquid surfactant will comprise from about 50% to 65% of the non-aqueous structured liquid phase. This corresponds to a non-aqueous liquid surfactant concentration in the total composition of from about 15% to 70% by weight, more preferably from about 20% to 50% by weight, of the composition.
 245

ii) Non-surfactant Non-aqueous Organic Solvents

The structured liquid phase of the detergent compositions prepared herein may also comprise one or more non-surfactant, non-aqueous organic solvents. Such
 250 non-surfactant non-aqueous liquids are preferably those of low polarity. For purposes of this invention, "low-polarity" liquids are those which have little, if any, tendency to dissolve one of the preferred types of particulate material used in the compositions prepared herein, i.e., the peroxygen bleaching agents, sodium perborate or sodium percarbonate. Thus relatively polar solvents such as ethanol are

255 preferably not utilized. Suitable types of low-polarity solvents useful in the non-aqueous liquid detergent compositions prepared herein do include non-vicinal C₄-C₈ alkylene glycols, alkylene glycol mono lower alkyl ethers, lower molecular weight polyethylene glycols, lower molecular weight methyl esters and amides, and the like.

260 A preferred type of non-aqueous, low-polarity solvent for use in the compositions prepared herein comprises the non-vicinal C₄-C₈ branched or straight chain alkylene glycols. Materials of this type include hexylene glycol (4-methyl-2,4-pentanediol), 1,6-hexanediol, 1,3-butylene glycol and 1,4-butylene glycol. Hexylene glycol is the most preferred.

265 Another preferred type of non-aqueous, low-polarity solvent for use herein comprises the mono-, di-, tri-, or tetra- C₂-C₃ alkylene glycol mono C₂-C₆ alkyl ethers. The specific examples of such compounds include diethylene glycol monobutyl ether, tetraethylene glycol monobutyl ether, dipropylene glycol monoethyl ether, and dipropylene glycol monobutyl ether. Diethylene glycol
270 monobutyl ether, dipropylene glycol monobutyl ether and butoxy-propoxy-propanol (BPP) are especially preferred. Compounds of the type have been commercially marketed under the tradenames Dowanol, Carbitol, and Cellosolve.

Another preferred type of non-aqueous, low-polarity organic solvent useful herein comprises the lower molecular weight polyethylene glycols (PEGs). Such
275 materials are those having molecular weights of at least about 150. PEGs of molecular weight ranging from about 200 to 600 are most preferred.

Yet another preferred type of non-polar, non-aqueous solvent comprises lower molecular weight methyl esters. Such materials are those of the general formula: R¹-C(O)-OCH₃ wherein R¹ ranges from 1 to about 18. Examples of suitable lower
280 molecular weight methyl esters include methyl acetate, methyl propionate, methyl octanoate, and methyl dodecanoate.

The non-aqueous, generally low-polarity, non-surfactant organic solvent(s) employed should, of course, be compatible and non-reactive with other composition components, e.g., bleach and/or activators, used in the liquid detergent compositions
285 prepared herein. Such a solvent component is preferably utilized in an amount of from about 1% to 70% by weight of the structured liquid phase. More preferably, a non-aqueous, low-polarity, non-surfactant solvent will comprise from about 10% to 60% by weight of the structured liquid phase, most preferably from about 20% to 50% by weight, of the structured liquid phase of the composition. Utilization of
290 non-surfactant solvent in these concentrations in the structured liquid phase corresponds to a non-surfactant solvent concentration in the total composition of

from about 1% to 50% by weight, more preferably from about 5% to 40% by weight, and most preferably from about 10% to 30% by weight, of the composition.

295 iii) Blends of Surfactant and Non-surfactant Solvents

In systems which employ both non-aqueous surfactant liquids and non-aqueous non-surfactant solvents, the ratio of surfactant to non-surfactant liquids, e.g., the ratio of alcohol alkoxylate to low polarity solvent, within the preferred structured, surfactant-containing liquid phase can be used to vary the rheological properties of the detergent compositions eventually formed. Generally, the weight ratio of
300 surfactant liquid to non-surfactant organic solvent will range about 50:1 to 1:50. More preferably, this ratio will range from about 3:1 to 1:3, most preferably from about 2:1 to 1:2.

305 (B) Surfactant Structurant

The surfactant-structured non-aqueous liquid phase of the preferred detergent compositions prepared in accordance with this invention is prepared by combining with the non-aqueous organic liquid diluents hereinbefore described a surfactant which is selected to add structure to the non-aqueous liquid phase of the detergent
310 compositions prepared herein. Structuring surfactants can be of the anionic, nonionic, cationic, and/or amphoteric types.

Preferred structuring surfactants are the anionic surfactants such as the alkyl sulfates, the alkyl polyalkxylate sulfates and the linear alkyl benzene sulfonates. Another common type of anionic surfactant material which may be optionally added
315 to the detergent compositions prepared herein as structurant comprises carboxylate-type anionics. Carboxylate-type anionics include the C₁₀-C₁₈ alkyl alkoxy carboxylates (especially the EO 1 to 5 ethoxycarboxylates) and the C₁₀-C₁₈ sarcosinates, especially oleoyl sarcosinate. Yet another common type of anionic surfactant material which may be employed as a structurant comprises other
320 sulfonated anionic surfactants such as the C₈-C₁₈ paraffin sulfonates and the C₈-C₁₈ olefin sulfonates. Structuring anionic surfactants will generally comprise from about 1% to 30% by weight of the compositions prepared herein.


As indicated, one preferred type of structuring anionic surfactant comprises primary or secondary alkyl sulfate anionic surfactants. Such surfactants are those
325 produced by the sulfation of higher C₈-C₂₀ fatty alcohols.

Conventional primary alkyl sulfate surfactants have the general formula



wherein R is typically a linear C₈ - C₂₀ hydrocarbyl group, which may be straight chain or branched chain, and M is a water-solubilizing cation. Preferably R is a C₁₀ - C₁₄ alkyl, and M is alkali metal. Most preferably R is about C₁₂ and M is sodium.


Conventional secondary alkyl sulfates may also be utilized as a structuring anionic surfactant for the liquid phase of the preferred compositions prepared herein. Conventional secondary alkyl sulfate surfactants are those materials which have the sulfate moiety distributed randomly along the hydrocarbyl "backbone" of the molecule. Such materials may be depicted by the structure:



wherein m and n are integers of 2 or greater and the sum of m + n is typically about 9 to 15, and M is a water-solubilizing cation.

If utilized, alkyl sulfates will generally comprise from about 1% to 30% by weight of the composition, more preferably from about 5% to 25% by weight of the composition. Non-aqueous liquid detergent compositions containing alkyl sulfates, peroxygen bleaching agents, and bleach activators are described in greater detail in Kong-Chan et al.; WO 96/10073; Published April 4, 1996, which application is incorporated herein by reference.

Another preferred type of anionic surfactant material which may be optionally added to the non-aqueous cleaning compositions prepared herein as a structurant comprises the alkyl polyalkoxylate sulfates. Alkyl polyalkoxylate sulfates are also known as alkoxylated alkyl sulfates or alkyl ether sulfates. Such materials are those which correspond to the formula



wherein R² is a C₁₀-C₂₂ alkyl group, m is from 2 to 4, n is from about 1 to 15, and M is a salt-forming cation. Preferably, R² is a C₁₂-C₁₈ alkyl, m is 2, n is from about 1 to 10, and M is sodium, potassium, ammonium, alkylammonium or alkanolammonium. Most preferably, R² is a C₁₂-C₁₆, m is 2, n is from about 1 to 6, and M is sodium. Ammonium, alkylammonium and alkanolammonium counterions are preferably avoided when used in the compositions prepared herein because of incompatibility with peroxygen bleaching agents.

If utilized, alkyl polyalkoxylate sulfates can also generally comprise from about 1% to 30% by weight of the composition, more preferably from about 5% to 25% by weight of the composition. Non-aqueous liquid detergent compositions containing alkyl polyalkoxylate sulfates, in combination with polyhydroxy fatty acid

amides, are described in greater detail in Boutique et al; PCT Application No. 365 PCT/US96/04223, which application is incorporated herein by reference.

The most preferred type of anionic surfactant for as a structurant use in the compositions prepared herein comprises the linear alkyl benzene sulfonate (LAS) surfactants. In particular, such LAS surfactants can be formulated into a specific type of anionic surfactant-containing powder which is especially useful for 370 incorporation into the preferred non-aqueous liquid detergent compositions of the present invention. Such a powder comprises two distinct phases. One of these phases is insoluble in the non-aqueous organic liquid diluents used in the compositions prepared herein; the other phase is soluble in the non-aqueous organic liquids. It is the insoluble phase of this preferred anionic surfactant-containing 375 powder which can be dispersed in the non-aqueous liquid phase of the preferred compositions prepared herein and which forms a network of aggregated small particles that allows the final product to stably suspend other additional solid particulate materials in the composition.

Such a preferred anionic surfactant-containing powder is formed by co-drying 380 an aqueous slurry which essentially contains a) one of more alkali metal salts of C₁₀₋₁₆ linear alkyl benzene sulfonic acids; and b) one or more non-surfactant diluent salts. Such a slurry is dried to a solid material, generally in powder form, which comprises both the soluble and insoluble phases.

The linear alkyl benzene sulfonate (LAS) materials used to form the preferred 385 anionic surfactant-containing powder are well known materials. Such surfactants and their preparation are described for example in U.S. Patents 2,220,099 and 2,477,383, incorporated herein by reference. Especially preferred are the sodium and potassium linear straight chain alkylbenzene sulfonates in which the average number of carbon atoms in the alkyl group is from about 11 to 14. Sodium C₁₁₋₃₉₀ C₁₄, e.g., C₁₂, LAS is especially preferred. The alkyl benzene surfactant anionic surfactants are generally used in the powder-forming slurry in an amount from about 20 to 70% by weight of the slurry, more preferably from about 30% to 60% by weight of the slurry.

The powder-forming slurry also contains a non-surfactant, organic or inorganic 395 salt component that is co-dried with the LAS to form the two-phase anionic surfactant-containing powder. Such salts can be any of the known sodium, potassium or magnesium halides, sulfates, citrates, carbonates, sulfates, borates, succinates, sulfo-succinates, xylene sulfonates, and the like. Sodium sulfate, which is generally a bi-product of LAS production, is the preferred non-surfactant diluent 400 salt for use herein. Salts which function as hydrotropes such as sodium sulfo-

succinate may also usefully be included. The non-surfactant salts are generally used in the aqueous slurry, along with the LAS, in amounts ranging from about 1 to 12% by weight of the slurry, more preferably from about 2% to 10% by weight of the slurry. Salts that act as hydrotropes can preferably comprise up to about 3% by weight of the slurry.

The aqueous slurry containing the LAS and diluent salt components hereinbefore described can be dried to form the anionic surfactant-containing powder preferably added to the non-aqueous diluents in order to prepare a structured liquid phase within the compositions prepared herein. Any conventional drying technique, e.g., spray drying, drum drying, etc., or combination of drying techniques, may be employed. Drying should take place until the residual water content of the solid material which forms is within the range of from about 0.5% to 4% by weight, more preferably from about 1% to 3% by weight.

The anionic surfactant-containing powder produced by the drying operation constitutes two distinct phases, one of which is soluble in the inorganic liquid diluents used herein and one of which is insoluble in the diluents. The insoluble phase in the anionic surfactant-containing powder generally comprises from about 10% to 60%, more preferably 10% to 25%, by weight of the powder, even more preferably from about 15% to 25% by weight of the powder.

The anionic surfactant-containing powder that results after drying comprises from about 45% to 90%, more preferably from about 80% to 94%, by weight of the powder of alkylbenzene sulfonic acid salts. Such concentrations are generally sufficient to provide from about 0.5% to 60%, more preferably from about 15% to 60%, by weight of the total detergent composition of the alkyl benzene sulfonic acid salts. The anionic surfactant-containing powder itself can comprise from about 0.45% to 45% by weight of the total composition. After drying, the anionic surfactant-containing powder will also contain from about 2% to 50%, more preferably from about 2% to 15%, by weight of the powder of the non-surfactant salts.

After it is dried to the requisite extent, the combined LAS/salt material can be converted to flakes or powder form by any known suitable milling or comminution process. Generally at the time such material is combined with the non-aqueous organic solvents to form the structured liquid phase of the compositions prepared herein, the particle size of this powder will range from 0.1 to 2000 microns, more preferably from about 0.1 to 1000 microns.

A structured, surfactant-containing liquid phase of the preferred detergent compositions prepared herein can be prepared by combining the non-aqueous

organic diluents hereinbefore described with the anionic surfactant-containing powder as hereinbefore described. Such combination results in the formation of a structured surfactant-containing liquid phase. Conditions for making this combination of preferred structured liquid phase components are described more fully hereinafter in the "Composition Preparation and Use" section. As previously noted, the formation of a structured, surfactant-containing liquid phase permits the stable suspension of additional functional particulate solid materials within the preferred detergent compositions prepared in accordance with this invention.

ADDITIONAL SOLID PARTICULATE MATERIALS

In addition to the non-aqueous liquid phase and the solid phase anionic surfactant materials preferably used to structure the liquid phase, the non-aqueous detergent compositions prepared herein also generally will comprise from about 5% to 55% by weight, more preferably from about 10% to 50% by weight, of additional solid phase particulate material which is dispersed and suspended within the liquid phase. In accordance with the process of this invention, such insoluble particulate material is used in composition preparation in the form of hydrated or hydrable salts that have a free, unbound moisture content of less than about 0.5%, preferably less than about 0.3%, when such material is combined with the liquid phase of the compositions prepared herein. Generally such particulate material will range in size from about 0.1 to 1500 microns, more preferably from about 0.1 to 900 microns. Most preferably, such material will range in size from about 5 to 200 microns.

The additional particulate material utilized in the process herein can comprise one or more types of detergent composition components which in particulate form are substantially insoluble in the non-aqueous liquid phase of the composition. The types of particulate materials which can be utilized are described in detail as follows:

(A) Peroxygen Bleaching Agent With Optional Bleach Activators

The most preferred type of particulate material useful in the detergent compositions prepared herein comprises particles of a peroxygen bleaching agent. Such peroxygen bleaching agents may be organic or inorganic in nature. Inorganic peroxygen bleaching agents are frequently utilized in combination with a bleach activator.

Useful organic peroxygen bleaching agents include percarboxylic acid bleaching agents and salts thereof. Suitable examples of this class of agents include magnesium monoperoxyphthalate hexahydrate, the magnesium salt of metachloro perbenzoic acid, 4-nonylamino-4-oxoperoxybutyric acid and diperoxydodecanedioic

475 acid. Such bleaching agents are disclosed in U.S. Patent 4,483,781, Hartman, Issued
November 20, 1984; European Patent Application EP-A-133,354, Banks et al.,
Published February 20, 1985; and U.S. Patent 4,412,934, Chung et al., Issued
November 1, 1983. Highly preferred bleaching agents also include 6-nonylamino-6-
480 oxoperoxypropionic acid (NAPAA) as described in U.S. Patent 4,634,551, Issued
January 6, 1987 to Burns et al.

Inorganic peroxygen bleaching agents may also be used in particulate form in
the detergent compositions prepared herein. Inorganic bleaching agents are in fact
preferred. Such inorganic peroxygen compounds include alkali metal perborate and
percarbonate materials, most preferably the percarbonates. For example, sodium
485 perborate (e.g. mono- or tetra-hydrate) can be used. Suitable inorganic bleaching
agents can also include sodium or potassium carbonate peroxyhydrate and
equivalent "percarbonate" bleaches, sodium pyrophosphate peroxyhydrate, urea
peroxyhydrate, and sodium peroxide. Persulfate bleach (e.g., OXONE,
manufactured commercially by DuPont) can also be used. Frequently inorganic
490 peroxygen bleaches will be coated with silicate, borate, sulfate or water-soluble
surfactants. For example, coated percarbonate particles are available from various
commercial sources such as FMC, Solvay Interlox, Tokai Denka and Degussa.

Inorganic peroxygen bleaching agents, e.g., the perborates, the percarbonates,
etc., are preferably combined with bleach activators, which lead to the *in situ*
495 production in aqueous solution (i.e., during use of the compositions prepared herein
for fabric laundering/bleaching) of the peroxy acid corresponding to the bleach
activator. Various non-limiting examples of activators are disclosed in U.S. Patent
4,915,854, Issued April 10, 1990 to Mao et al.; and U.S. Patent 4,412,934 Issued
November 1, 1983 to Chung et al. The nonanoyloxybenzene sulfonate (NOBS) and
500 tetraacetyl ethylene diamine (TAED) activators are typical. Mixtures thereof can
also be used. See also the hereinbefore referenced U.S. 4,634,551 for other typical
bleaches and activators useful herein.

Other useful amido-derived bleach activators are those of the formulae:




wherein R^1 is an alkyl group containing from about 6 to about 12 carbon atoms, R^2
is an alkylene containing from 1 to about 6 carbon atoms, R^5 is H or alkyl, aryl, or
alkaryl containing from about 1 to about 10 carbon atoms, and L is any suitable
510 leaving group. A leaving group is any group that is displaced from the bleach


activator as a consequence of the nucleophilic attack on the bleach activator by the perhydrolysis anion. A preferred leaving group is phenol sulfonate.

Preferred examples of bleach activators of the above formulae include (6-octanamido-caproyl)oxybenzenesulfonate, (6-nonanamidocaproyl)oxybenzenesulfonate, (6-decanamido-caproyl)oxybenzenesulfonate and mixtures thereof as described in the hereinbefore referenced U.S. Patent 4,634,551. Such mixtures are characterized herein as (6-C₈-C₁₀ alkamido-caproyl)oxybenzenesulfonate.

Another class of useful bleach activators comprises the benzoxazin-type activators disclosed by Hodge et al. in U.S. Patent 4,966, 723, Issued October 30, 1990, incorporated herein by reference. A highly preferred activator of the benzoxazin-type is:



Still another class of useful bleach activators includes the acyl lactam activators, especially acyl caprolactams and acyl valerolactams of the formulae:



wherein R⁶ is H or an alkyl, aryl, alkoxyaryl, or alkaryl group containing from 1 to about 12 carbon atoms. Highly preferred lactam activators include benzoyl caprolactam, octanoyl caprolactam, 3,5,5-trimethylhexanoyl caprolactam, nonanoyl caprolactam, decanoyl caprolactam, undecenoyl caprolactam, benzoyl valerolactam, octanoyl valerolactam, decanoyl valerolactam, undecenoyl valerolactam, 3,5,5-trimethylhexanoyl valerolactam and mixtures thereof. See also U.S. Patent 4,545,784, Issued to Sanderson, October 8, 1985, incorporated herein by reference, which discloses acyl caprolactams, including benzoyl caprolactam, adsorbed into sodium perborate.

If peroxygen bleaching agents are used as all or part of the essentially present additional particulate material, they will generally comprise from about 1% to 30% by weight of the composition. More preferably, peroxygen bleaching agent will comprise from about 5% to 20% by weight of the composition. Most preferably, peroxygen bleaching agent will be present to the extent of from about 5% to 20% by

weight of the composition. If utilized, bleach activators can comprise from about 0.5% to 20%, more preferably from about 3% to 10%, by weight of the composition. Frequently, activators are employed such that the molar ratio of bleaching agent to activator ranges from about 1:1 to 10:1, more preferably from about 1.5:1 to 5:1.

545 In addition, it has been found that bleach activators, when agglomerated with certain acids such as citric acid, are more chemically stable.

(B) Organic Builder Material

Another possible type of additional particulate material which can be
550 suspended in the non-aqueous liquid detergent compositions prepared herein comprises an organic detergent builder material which serves to counteract the effects of calcium, or other ion, water hardness encountered during laundering/bleaching use of the compositions prepared herein. Examples of such materials include the alkali metal, citrates, succinates, malonates, fatty acids,
555 carboxymethyl succinates, carboxylates, polycarboxylates and polyacetyl carboxylates. Specific examples include sodium, potassium and lithium salts of oxydisuccinic acid, mellitic acid, benzene polycarboxylic acids and citric acid. Other examples of organic phosphonate type sequestering agents such as those which have been sold by Monsanto under the Dequest tradename and alkanehydroxy
560 phosphonates. Citrate salts are highly preferred.

Other suitable organic builders include the higher molecular weight polymers and copolymers known to have builder properties. For example, such materials include appropriate polyacrylic acid, polymaleic acid, and polyacrylic/polymaleic acid copolymers and their salts, such as those sold by BASF under the Sokalan
565 trademark which have molecular weight ranging from about 5,000 to 100,000.

Another suitable type of organic builder comprises the water-soluble salts of higher fatty acids, i.e., "soaps". These include alkali metal soaps such as the sodium, potassium, ammonium, and alkylammonium salts of higher fatty acids containing from about 8 to about 24 carbon atoms, and preferably from about 12 to about 18
570 carbon atoms. Soaps can be made by direct saponification of fats and oils or by the neutralization of free fatty acids. Particularly useful are the sodium and potassium salts of the mixtures of fatty acids derived from coconut oil and tallow, i.e., sodium or potassium tallow and coconut soap.

If utilized as all or part of the additional particulate material, insoluble organic
575 detergent builders can generally comprise from about 2% to 20% by weight of the compositions prepared herein. More preferably, such builder material can comprise from about 4% to 10% by weight of the composition.

(C) Inorganic Alkalinity Sources

580 Another possible type of additional particulate material which can be
suspended in the non-aqueous liquid detergent compositions prepared herein can
comprise a material which serves to render aqueous washing solutions formed from
such compositions generally alkaline in nature. Such materials may or may not also
act as detergent builders, i.e., as materials which counteract the adverse effect of
585 water hardness on detergency performance.

Examples of suitable alkalinity sources include water-soluble alkali metal
carbonates, bicarbonates, borates, silicates and metasilicates. Although not preferred
for ecological reasons, water-soluble phosphate salts may also be utilized as
alkalinity sources. These include alkali metal pyrophosphates, orthophosphates,
590 polyphosphates and phosphonates. Of all of these alkalinity sources, alkali metal
carbonates such as sodium carbonate are the most preferred.

The alkalinity source, if in the form of a hydratable salt, may also serve as a
desiccant in the non-aqueous liquid detergent compositions prepared herein. The
presence of an alkalinity source which is also a desiccant may provide benefits in
595 terms of chemically stabilizing those composition components such as the
peroxygen bleaching agent which may be susceptible to deactivation by water.

If utilized as all or part of the additional particulate material component, the
alkalinity source will generally comprise from about 1% to 25% by weight of the
compositions prepared herein. More preferably, the alkalinity source can comprise
600 from about 5% to 15% by weight of the composition. Such materials, while water-
soluble, will generally be insoluble in the non-aqueous detergent compositions
prepared herein. Thus such materials will generally be dispersed in the non-aqueous
liquid phase in the form of discrete particles.

605 OPTIONAL COMPOSITION COMPONENTS

In addition to the essentially utilized composition liquid and solid phase
components as hereinbefore described, the detergent compositions prepared herein
can, and preferably will, contain various optional components. Such optional
components may be in either liquid or solid form. The optional components may
610 either dissolve in the liquid phase or may be dispersed within the liquid phase in the
form of fine particles or droplets. Some of the materials which may optionally be
utilized in the compositions prepared herein are described in greater detail as
follows:

615 (a) Optional Inorganic Detergent Builders

The detergent compositions prepared herein may also optionally contain one or more types of inorganic detergent builders beyond those listed hereinbefore that also function as alkalinity sources. Such optional inorganic builders can include, for example, aluminosilicates such as zeolites. Aluminosilicate zeolites, and their use as
620 detergent builders are more fully discussed in Corkill et al., U.S. Patent No. 4,605,509; Issued August 12, 1986, the disclosure of which is incorporated herein by reference. Also crystalline layered silicates, such as those discussed in this '509 U.S. patent, are also suitable for use in the detergent compositions prepared herein. If utilized, optional inorganic detergent builders can comprise from about 2% to
625 15% by weight of the compositions prepared herein.

(b) Optional Enzymes

The detergent compositions prepared herein may also optionally contain one or more types of detergent enzymes. Such enzymes can include proteases, amylases,
630 cellulases and lipases. Such materials are known in the art and are commercially available. They may be incorporated into the non-aqueous liquid detergent compositions prepared herein in the form of suspensions, "marumes" or "prills". Another suitable type of enzyme comprises those in the form of slurries of enzymes in nonionic surfactants, e.g., the enzymes marketed by Novo Nordisk under the
635 tradename "SL" or the microencapsulated enzymes marketed by Novo Nordisk under the tradename "LDP."

Enzymes added to the compositions prepared herein in the form of conventional enzyme prills are especially preferred for use herein. Such prills will generally range in size from about 100 to 1,000 microns, more preferably from about
640 200 to 800 microns and will be suspended throughout the non-aqueous liquid phase of the composition. Prills in the compositions of the present invention have been found, in comparison with other enzyme forms, to exhibit especially desirable enzyme stability in terms of retention of enzymatic activity over time. Thus, compositions which utilize enzyme prills need not contain conventional enzyme
645 stabilizing such as must frequently be used when enzymes are incorporated into aqueous liquid detergents.

If employed, enzymes will normally be incorporated into the non-aqueous liquid compositions prepared herein at levels sufficient to provide up to about 10 mg by weight, more typically from about 0.01 mg to about 5 mg, of active enzyme per
650 gram of the composition. Stated otherwise, the non-aqueous liquid detergent compositions prepared herein will typically comprise from about 0.001% to 5%,

preferably from about 0.01% to 1% by weight, of a commercial enzyme preparation. Protease enzymes, for example, are usually present in such commercial preparations at levels sufficient to provide from 0.005 to 0.1 Anson units (AU) of activity per
655 gram of composition.

(c) Optional Chelating Agents

The detergent compositions prepared herein may also optionally contain a chelating agent which serves to chelate metal ions, e.g., iron and/or manganese,
660 within the non-aqueous detergent compositions prepared herein. Such chelating agents thus serve to form complexes with metal impurities in the composition which would otherwise tend to deactivate composition components such as the peroxygen bleaching agent. Useful chelating agents can include amino carboxylates, phosphonates, amino phosphonates, polyfunctionally-substituted aromatic chelating
665 agents and mixtures thereof.

Amino carboxylates useful as optional chelating agents include ethylenediaminetetraacetates, N-hydroxyethyl-ethylenediaminetriacetates, nitrilotriacetates, ethylene-diamine tetrapropionates, triethylenetetraaminehexacetates, diethylenetriaminepentaacetates,
670 ethylenediaminedisuccinates and ethanol diglycines. The alkali metal salts of these materials are preferred.

Amino phosphonates are also suitable for use as chelating agents in the compositions of this invention when at least low levels of total phosphorus are permitted in detergent compositions, and include ethylenediaminetetrakis
675 (methylene-phosphonates) as DEQUEST. Preferably, these amino phosphonates do not contain alkyl or alkenyl groups with more than about 6 carbon atoms.

Preferred chelating agents include hydroxy-ethyldiphosphonic acid (HEDP), diethylene triamine penta acetic acid (DTPA), ethylenediamine disuccinic acid (EDDS) and dipicolinic acid (DPA) and salts thereof. The chelating agent may, of
680 course, also act as a detergent builder during use of the compositions prepared herein for fabric laundering/bleaching. The chelating agent, if employed, can comprise from about 0.1% to 4% by weight of the compositions prepared herein. More preferably, the chelating agent will comprise from about 0.2% to 2% by weight of the detergent compositions prepared herein.

685

690 (d) Optional Thickening, Viscosity Control and/or
Dispersing Agents

The detergent compositions prepared herein may also optionally contain a polymeric material which serves to enhance the ability of the composition to maintain its solid particulate components in suspension. Such materials may thus act as thickeners, viscosity control agents and/or dispersing agents. Such materials
695 are frequently polymeric polycarboxylates but can include other polymeric materials such as polyvinylpyrrolidone (PVP) or polyamide resins. Insoluble materials like fumed silica and titanium dioxide may also be used to enhance the elasticity of any structured liquid phase that is present.

Polymeric polycarboxylate materials can be prepared by polymerizing or
700 copolymerizing suitable unsaturated monomers, preferably in their acid form. Unsaturated monomeric acids that can be polymerized to form suitable polymeric polycarboxylates include acrylic acid, maleic acid (or maleic anhydride), fumaric acid, itaconic acid, aconitic acid, mesaconic acid, citraconic acid and methylenemalononic acid. The presence in the polymeric polycarboxylates herein of
705 monomeric segments, containing no carboxylate radicals such as vinylmethyl ether, styrene, ethylene, etc. is suitable provided that such segments do not constitute more than about 40% by weight of the polymer.

Particularly suitable polymeric polycarboxylates can be derived from acrylic acid. Such acrylic acid-based polymers which are useful herein are the water-
710 soluble salts of polymerized acrylic acid. The average molecular weight of such polymers in the acid form preferably ranges from about 2,000 to 100,000, more preferably from about 2,000 to 10,000, even more preferably from about 4,000 to 7,000, and most preferably from about 4,000 to 5,000. Water-soluble salts of such acrylic acid polymers can include, for example, the alkali metal, salts. Soluble
715 polymers of this type are known materials. Use of polyacrylates of this type in detergent compositions has been disclosed, for example, Diehl, U.S. Patent 3,308,067, issued March 7, 1967. Such materials may also perform a builder function.

If utilized, the optional thickening, viscosity control and/or dispersing agents
720 should be present in the compositions prepared herein to the extent of from about 0.1% to 4% by weight. More preferably, such materials can comprise from about 0.5% to 2% by weight of the detergents compositions prepared herein.

725

(e) Optional Clay Soil Removal/Anti-redeposition Agents

The compositions prepared in accordance with the present invention can also optionally contain water-soluble ethoxylated amines having clay soil removal and anti-redeposition properties. If used, soil materials can contain from about 0.01% to
730 about 5% by weight of the compositions prepared herein.

The most preferred soil release and anti-redeposition agent is ethoxylated tetraethylenepentamine. Exemplary ethoxylated amines are further described in U.S. Patent 4,597,898, VanderMeer, issued July 1, 1986. Another group of preferred clay soil removal-anti-redeposition agents are the cationic compounds disclosed in
735 European Patent Application 111,965, Oh and Gosselink, published June 27, 1984. Other clay soil removal/anti-redeposition agents which can be used include the ethoxylated amine polymers disclosed in European Patent Application 111,984, Gosselink, published June 27, 1984; the zwitterionic polymers disclosed in European Patent Application 112,592, Gosselink, published July 4, 1984; and the
740 amine oxides disclosed in U.S. Patent 4,548,744, Connor, issued October 22, 1985. Other clay soil removal and/or anti-redeposition agents known in the art can also be utilized in the compositions prepared herein. Another type of preferred anti-redeposition agent includes the carboxy methyl cellulose (CMC) materials. These materials are well known in the art.

745

(f) Optional Liquid Bleach Activators

The detergent compositions prepared herein may also optionally contain bleach activators which are liquid in form at room temperature and which can be added as liquids to the non-aqueous liquid phase of the detergent compositions herein. One
750 such liquid bleach activator is acetyl triethyl citrate (ATC). Other examples include glycerol triacetate and nonanoyl valerolactam. Liquid bleach activators can be dissolved in the non-aqueous liquid phase of the compositions prepared herein.

(g) Optional Brighteners, Suds Suppressors, Dyes and/or Perfumes

The detergent compositions prepared herein may also optionally contain
755 conventional brighteners, suds suppressors, bleach catalysts, dyes and/or perfume materials. Such brighteners, suds suppressors, silicone oils, bleach catalysts, dyes and perfumes must, of course, be compatible and non-reactive with the other composition components in a non-aqueous environment. If present, brighteners suds
760 suppressors, dyes and/or perfumes will typically comprise from about 0.0001% to 2% by weight of the compositions prepared herein. Suitable bleach catalysts include

the manganese based complexes disclosed in US 5,246,621, US 5,244,594, US 5,114,606 and US 5,114,611.

765 COMPOSITION FORM

As indicated, the non-aqueous liquid detergent compositions prepared herein are in the form of bleaching agent and/or other materials in particulate form as a solid phase suspended in and dispersed throughout a surfactant-containing, structured non-aqueous liquid phase. Generally, the structured non-aqueous liquid
770 phase will comprise from about 45% to 95%, more preferably from about 50% to 90%, by weight of the composition with the dispersed additional solid materials comprising from about 5% to 55%, more preferably from about 10% to 50%, by weight of the composition.

The particulate-containing liquid detergent compositions prepared in
775 accordance with this invention are substantially non-aqueous (or anhydrous) in character. While very small amounts of water may be incorporated into such compositions as an impurity in the essential or optional components, the amount of water should in no event exceed about 5% by weight of the compositions prepared herein. More preferably, water content of the non-aqueous detergent compositions
780 prepared herein will comprise less than about 1% by weight.

The particulate-containing non-aqueous liquid detergent compositions prepared herein will be relatively viscous and phase stable under conditions of commercial marketing and use of such compositions. Frequently the viscosity of the compositions prepared herein will range from about 300 to 5,000 cps, more
785 preferably from about 500 to 3,000 cps. For purposes of this invention, viscosity is measured with a Carrimed CSL2 Rheometer at a shear rate of 20 s^{-1} .

COMPOSITION PREPARATION AND USE

The non-aqueous liquid detergent compositions prepared herein can be
790 prepared by first forming the structured, surfactant-containing non-aqueous liquid phase and by thereafter adding to this structured phase the additional particulate components in any convenient order and by mixing, e.g., agitating, the resulting component combination to form the phase stable compositions prepared herein. In a typical process for preparing such compositions, essential and certain preferred
795 optional components will be combined in a particular order and under certain conditions.

In a first step of a preferred preparation process, the anionic surfactant-containing powder used to form the structured, surfactant-containing liquid phase is

800 prepared. This pre-preparation step involves the formation of an aqueous slurry containing from about 30% to 60% of one or more alkali metal salts of linear C₁₀₋₁₆ alkyl benzene sulfonic acid and from about 2% to 10% of one or more diluent non-surfactant salts. In a subsequent step, this slurry is dried to the extent necessary to form a solid material containing less than about 4% by weight of residual water.

805 After preparation of this solid anionic surfactant-containing material, this material can be combined with one or more of the non-aqueous organic diluents to form the structured, surfactant-containing liquid phase of the detergent compositions prepared herein. This is done by reducing the anionic surfactant-containing material formed in the previously described pre-preparation step to powdered form and by combining such powdered material with an agitated liquid medium comprising one
810 or more of the non-aqueous organic diluents, either surfactant or non-surfactant or both, as hereinbefore described. This combination is carried out under agitation conditions which are sufficient to form a thoroughly mixed dispersion of particles of the insoluble fraction of the co-dried LAS/salt material throughout a non-aqueous organic liquid diluent.

815 In a subsequent processing step, the non-aqueous liquid dispersion so prepared can then be subjected to milling or high shear agitation under conditions which are sufficient to provide the structured, surfactant-containing liquid phase of the detergent compositions prepared herein. Such milling or high shear agitation conditions will generally include maintenance of a temperature between about 10°C
820 and 90°C, preferably between about 20°C and 60°C; and a processing time that is sufficient to form a network of aggregated small particles of the insoluble fraction of the anionic surfactant-containing powdered material. Suitable equipment for this purpose includes: stirred ball mills, co-ball mills (Fryma), colloid mills, high pressure homogenizers, high shear mixers, and the like. The colloid mill and high
825 shear mixers are preferred for their high throughput and low capital and maintenance costs. The small particles produced in such equipment will generally range in size from about 0.4 to 2 microns. Milling and high shear agitation of the liquid/solids combination will generally provide an increase in the yield value of the structured liquid phase to within the range of from about 1 Pa to 8 Pa, preferably from about 1
830 Pa to 4 Pa.

After formation of the dispersion of LAS/salt co-dried material in the non-aqueous liquid, either before or after such dispersion is milled or agitated to increase its yield value, the additional particulate material to be used in the detergent compositions prepared herein can be added. Such components which can be added
835 under high shear agitation include the silica or titanium dioxide; particles of

substantially all of an organic builder, e.g., citrate and/or fatty acid, and/or an alkalinity source, e.g., sodium carbonate, can be added while continuing to maintain this admixture of composition components under shear agitation. Agitation of the mixture is continued, and if necessary, can be increased at this point to form a
840 uniform dispersion of insoluble solid phase particulates within the liquid phase.

After some or all of the foregoing solid materials have been added to this agitated mixture, the particles of the highly preferred peroxygen bleaching agent can be added to the composition, again while the mixture is maintained under shear agitation. By adding the peroxygen bleaching agent material last, or after all or most
845 of the other components, and especially after alkalinity source particles, have been added, desirable stability benefits for the peroxygen bleach can be realized. If enzyme prills are incorporated, they are preferably added to the non-aqueous liquid matrix last.

As a final process step, after addition of all of the particulate material, agitation
850 of the mixture is continued for a period of time sufficient to form compositions having the requisite viscosity, yield value and phase stability characteristics. Frequently this will involve agitation for a period of from about 1 to 30 minutes.

In adding solid components to non-aqueous liquids in accordance with the present invention, it is essential to maintain the free, unbound moisture content of
855 these solid materials below certain limits. Free moisture in such solid materials is frequently present at levels of 0.8% or greater. By reducing free moisture content, e.g., by fluid bed drying, of solid particulate materials to a free moisture level of less than about 0.5% prior to their incorporation into the detergent composition matrix, significant stability advantages for the resulting composition can be realized.

The compositions of this invention, prepared as hereinbefore described, can be used to form aqueous washing solutions for use in the laundering and bleaching of fabrics. Generally, an effective amount of such compositions is added to water, preferably in a conventional fabric laundering automatic washing machine, to form such aqueous laundering/bleaching solutions. The aqueous washing/bleaching
860 solution so formed is then contacted, preferably under agitation, with the fabrics to be laundered and bleached therewith.

An effective amount of the liquid detergent compositions prepared herein added to water to form aqueous laundering/bleaching solutions can comprise amounts sufficient to form from about 500 to 7,000 ppm of composition in aqueous
870 solution. More preferably, from about 800 to 3,000 ppm of the detergent compositions prepared herein will be provided in aqueous washing/bleaching solution.

875 The following examples illustrate the preparation and performance advantages of non-aqueous liquid detergent compositions of the instant invention. Such examples, however, are not necessarily meant to limit or otherwise define the scope of the invention herein.

880

EXAMPLE I

Preparation of LAS Powder

885 Sodium C₁₂ linear alkyl benzene sulfonate (NaLAS) is processed into a powder containing two phases. One of these phases is soluble in the non-aqueous liquid detergent compositions prepared herein and the other phase is insoluble. It is the insoluble fraction which serves to add structure and particle suspending capability to the non-aqueous phase of the compositions prepared herein.

890 NaLAS powder is produced by taking a slurry of NaLAS in water (approximately 40-50% active) combined with dissolved sodium sulfate (3-15%) and a hydrotrope, sodium sulfosuccinate (1-3%). The hydrotrope and sulfate are used to improve the characteristics of the dry powder. A drum dryer is used to dry the slurry into a flake. When the NaLAS is dried with the sodium sulfate, two distinct phases are created within the flake. The insoluble phase creates a network structure of aggregate small particles (0.4-2 μ m) which allows the finished non-aqueous detergent product to stably suspend solids.

The NaLAS powder prepared according to this example has the following makeup shown in Table I.

900

TABLE I
LAS Powder

<u>Component</u>	<u>Wt. %</u>
NaLAS	85%
Sulfate	11%
Sulfosuccinate	2%

Water	2.5%
Unreacted, etc.	balance to 100%
% insoluble LAS	17%
# of phase (via X-ray diffraction)	2

EXAMPLE II

905

Preparation of Non-Aqueous Liquid Detergent Composition

- 1) Butoxy-propoxy-propanol (BPP) and a C₁₁₋₁₅EO(5) ethoxylated alcohol nonionic surfactant (Neodol 1-5) are mixed for a short time (1-2 minutes) using a pitched blade turbine impeller in a mix tank into a single phase.
- 910 2) NaLAS powder as prepared in Example I is added to the BPP/Neodol solution in the mix tank to partially dissolve the NaLAS. Mix time is approximately one hour. The tank is blanketed with nitrogen to prevent moisture pickup from the air. The soluble phase of NaLAS powder dissolves, while the insoluble NaLAS aggregates and forms a network structure within the BPP/Neodol
915 solution.
- 3) Liquid base (LAS/BPP/NI) is pumped out into drums. Molecular sieves (type 3A, 4-8 mesh) are added to each drum at 10% of the net weight of the liquid base. The molecular sieves are mixed into the liquid base using both single blade turbine mixers and drum rolling techniques. The mixing is done under
920 nitrogen blanket to prevent moisture pickup from the air. Total mix time is 2 hours, after which 0.1-0.4% of the moisture in the liquid base is removed.
- 4) Molecular sieves are removed by passing the liquid base through a 20-30 mesh screen. Liquid base is returned to the mix tank.
- 5) Additional solid ingredients are prepared for addition to the composition. For
925 those ingredients in the form of hydrated or hydratable salts, these ingredients are dried in a fluidized bed dryer to a free moisture content of less 0.5%. Such solid ingredients include the following:

Sodium carbonate (particle size 10-40 microns)

Sodium citrate dihydrate

930

Maleic-acrylic copolymer (BASF's Sokalan CP5)

Brightener

Titanium dioxide particles (1-5 microns)

Diethyl triamine pentaacetic acid (DTPA)

935

These solid materials, which are all millable, are added to the mix tank through a 20-30 mesh screen and mixed with the liquid base until smooth. This approximately 1 hour after addition of the last powder. The tank is blanketed with nitrogen after addition of the powders. No particular order of addition for these powders is critical.

940

- 6) The batch is pumped once through a Fryma colloid mill, which is a simple rotor-stator configuration in which a high-speed rotor spins inside a stator which creates a zone of high shear. This serves to disperse the insoluble NaLAS aggregates and partially reduce the particle size of all of the solids. This leads to an increase in yield value (i.e. structure). The batch is then recharged to the mix tank.

945

- 7) Still additional solid materials which should not be milled or subjected to high shear agitation are then prepared. Again hydrated and hydratable salts are fluidized bed dried to a free moisture content of less than 0.5%. These include the following.

950

Sodium nonanoyloxybenzene sulfonate (NOBS) coated with

Sodium citrate dihydrate

NOBS 60%

Citrate 40%

Sodium perborate (20-40 microns)

Protease and amylase enzyme prills (100-1000 microns)

955

These non-millable solid materials are then added to the mix tank followed by liquid ingredients (perfume and silicone-based suds suppressor). The batch is then mixed for one hour (under nitrogen blanket). The resulting composition has the formula set forth in Table II.

960

TABLE II

N n-Aqueous Liquid Detergent Composition with Bleach

<u>Component</u>	<u>Wt % Active</u>
LAS Powder	20.26
C ₁₂₋₁₄ E ₀₌₅ alcohol ethoxylate	18.82
BPP	18.82
Sodium citrate dihydrate	4.32
Citrate Coated NOBS	8.49
Sodium Carbonate	11.58
Maleic-acrylic copolymer	11.58
DTPA	0.77
Protease Prills	0.77
Amylase Prills	0.39
Sodium Perborate	2.86
Suds Suppressor	0.03
Perfume	0.46
Titanium Dioxide	0.54
Brightener	<u>0.31</u>
	100.00%

965 The resulting Table II composition is a stable, anhydrous heavy-duty liquid laundry detergent which provides excellent stain and soil removal performance when used in normal fabric laundering operations.

EXAMPLE III**Effect of Pre-drying Solid Components**

970 Formulas similar to that shown in Example III, Table II are prepared but with the Sokalan maleic-acrylic copolymer having varying levels of free moisture prior to its addition to the product formula and with the formula itself either not subjected or

975 subjected to the molecular sieve drying procedure described in Example III. In two cases, the Sokalan CP5 maleic-acrylic copolymer is fluid bed dried (120°C for 30 minutes) prior to its addition to the test formula; in two other cases the Sokalan CP5 is not dried. Fluid bed drying of the Sokalan reduces its total moisture content from 10% to about 4%. At 4% moisture, all of the water is believed to be bound water of hydration, thereby resulting in a free moisture content of the Sokalan of less than 0.5%.

980 The several test formulas as hereinbefore described are evaluated for percent of retained peracid in a 4-week aging test. Test formulas, moisture content of the maleic-acrylic copolymer and bleach stability results are shown in Table III.

TABLE III

985

Test Formula	Table IIA	Table IIB	Table IIC	TableIID
Molecular Sieve Treated	No	No	Yes	Yes
Total Moisture in Sokalan	10%	4%	10%	4%
Free Moisture in Sokalan	6%	<0.5%	6%	<0.5%
% of Peracid Retained after 4 weeks at 100°F	71.1%	83.0%	74.4%	86.3%

The Table III data illustrate the beneficial effect on bleach stability which can be realized by pre-drying one of the solid components prior to its incorporation into non-aqueous liquid detergents in accordance with the process of this invention.

990 WHAT IS CLAIMED IS:

1. A process for preparing non-aqueous liquid heavy-duty detergent compositions of improved chemical stability, which process comprises the steps of:
 - A) forming a liquid base comprising one or more non-aqueous liquid organic diluents;
 - 995 B) providing, for eventual combination with said liquid base, one or more types of hydrated or hydratable particulate components which are selected from anionic surfactants, peroxygen bleaching agents, bleach activators, organic detergent builders and inorganic alkalinity sources; which range in particle size from about 0.1 to 1500 microns; and which
1000 have an initial free, unbound moisture content of about 0.5% by weight or greater;
 - C) drying said hydrated or hydratable particulate components using a fluidized bed drying procedure to thereby reduce the free, unbound moisture content of said particulate components to a level of less than
1005 about 0.5% by weight; and immediately thereafter
 - D) combining said dried hydrated or hydratable particulate components with said liquid base,

to thereby form said non-aqueous liquid detergent compositions.
2. A process according to Claim 1 wherein said hydrated or hydratable particulate
1010 components include an anionic surfactant-containing powder which is formed by co-drying:
 - a) one or more alkali metal salts of C₁₀₋₁₆ linear alkyl benzene sulfonic acids; and
 - b) one or more non-surfactant salts;
1015 to produce a powder which contains from about 45% to 94% by weight of said powder of said alkyl benzene sulfonic acid salts, from about 2% to 50% by weight of said powder of said non-surfactant salts and from about 0.5% to 4% by weight of said powder of residual water; and which contains from about 10% to 60% by weight of said powder of a solid phase which is insoluble in said non-
1020 aqueous organic diluents.
3. A process according to Claim 2 wherein said hydrated or hydratable particulate components also includes additional particulate material which

- 1025 ranges in size from 0.1 to 900 microns, which is substantially insoluble in said liquid base and which is selected from peroxygen bleaching agents, bleach activators, ancillary anionic surfactants, organic detergent builders and inorganic alkalinity sources and combinations of said additional particulate material types.
- 1030 4. A process according to Claim 3 wherein in Step D the combining of said particulate components with said liquid base forms a structured, surfactant-containing liquid phase which is subjected to milling or high shear agitation at a temperature from about 20°C to 60°C, said milling or high shear agitation being sufficient to increase the yield value of said structured, surfactant-containing liquid phase to a level within the range from about 1 Pa to 8 Pa, to thereby form said non-aqueous liquid detergent composition.
- 1035 5. A process according to Claim 4 wherein
- (A) the alkyl group of said alkylbenzene sulfonic acid is linear and contains from about 11 to 14 carbon atoms;
- (B) the non-surfactant salts are selected from alkali metal sulfates, citrates, carbonates and xylene sulfonates;
- 1040 (C) the liquid base comprises both a non-aqueous liquid nonionic surfactant and a non-aqueous low polarity non-surfactant solvent; and
- (D) said additional particulate material comprises peroxygen bleaching agents selected from percarboxylic acids and salts thereof and alkali metal perborates and percarbonates.
- 1045 6. A process according to Claim 5 wherein
- (A) said alkylbenzene sulfonate surfactant comprises from about 15% to 60% by weight of the composition that is eventually formed;
- (B) said nonaqueous liquid base comprises from about 15% to 70% by weight of the composition eventually formed and utilizes an alcohol alkoxylate liquid nonionic surfactant in a ratio to non-surfactant solvent of from about 3:1 to 1:3; and
- 1050 (C) said additional particulate material comprises from about 5% to 50% by weight of the composition that is eventually formed.
- 1055 7. A process according to Claim 6 wherein

- (A) said peroxygen bleaching agent is selected from alkali metal perborates and percarbonates and comprises from about 1% to 30% by weight of the composition that is eventually formed; and
- (B) said additional particulate material also comprises from 0.5% to 20%, by weight of the composition eventually formed, of particles of a bleach activator which can react with said peroxygen bleaching agent to form a peroxy acid.
- 1060
8. A process according to Claim 7 wherein
- (A) said alcohol alkoxylate nonionic surfactant comprises ethoxylated materials containing from about 8 to 15 carbon atoms and having from about 3 to 10 ethylene oxide moieties per molecule; and
- 1065
- (B) said nonaqueous low-polarity non-surfactant solvent is selected from
- i) mono, di, tri, tetra C₂-C₃ alkylene glycol mono C₂-C₆ alkyl ethers; and
- ii) non-vicinal alkylene glycols containing from 4 to 8 carbon atoms.
- 1070
9. A process according to Claim 8 wherein said additional particulate material also comprises from about 2% to 20%, by weight of the composition eventually formed, of an organic detergent builder selected from alkali metal citrates, succinates, malonates, carboxymethylsuccinates, carboxylates, polycarboxylates, polyacetylcarboxylates and fatty acid soaps.
- 1075
10. A process according to Claim 9 wherein said organic detergent builder is selected from sodium citrate and poly-acrylate/maleate copolymers of molecular weight ranging from about 5,000 to 100,000.
- 1080
11. A process according to Claim 10 wherein said additional particulate material also comprises from about 1% to 25%, by weight of the composition eventually formed, of an alkalinity source selected from water-soluble alkali metal carbonates, bicarbonates, borates, silicates and metasilicates.
12. A process according to Claim 11 wherein said alkalinity source is sodium carbonate.
- 1085
13. A process according to Claim 8 wherein the composition that is formed has from about 50% to 75% by weight of the composition of a liquid phase and from about 25% to 50% by weight of the composition of a solid particulate phase.

14. A process according to Claim 8 wherein the composition that is formed has a viscosity of from about 500 to 3,000 cps.

1090

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 97/10790

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: C11D 17/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: C11D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, CA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	WO 9700938 A1 (THE PROCTER & GAMBLE COMPANY), 9 January 1997 (09.01.97), the whole document --	1-14
A	WO 9610072 A1 (THE PROCTER & GAMBLE COMPANY), 4 April 1996 (04.04.96) --	1-14
A	WO 9113139 A1 (UNILEVER PLC), 5 Sept 1991 (05.09.91) --	1-14
A	WO 9209678 A1 (S.B. CHEMICALS LIMITED), 11 June 1992 (11.06.92) -- -----	1-14

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- * "A" document defining the general state of the art which is not considered to be of particular relevance
- * "E" earlier document but published on or after the international filing date
- * "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- * "O" document referring to an oral disclosure, use, exhibition or other means
- * "P" document published prior to the international filing date but later than the priority date claimed

* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

* "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

* "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

* "&" document member of the same patent family


Date of the actual completion of the international search

14 October 1997

Date of mailing of the international search report

06. 11. 97

Name and mailing address of the ISA/

 European Patent Office, P.B. 5818 Patentlaan 2
NL-2280 HV Rijswijk
Tel.: (31-70) 340-2040, Tx. 31 651 cpo nl.
Fax: (31-70) 340-3016

Authorized officer

DAGMAR JÄRVMAN

INTERNATIONAL SEARCH REPORT

16570

Information on patent family members

01/09/97

International application No.

PCT/US 97/10790

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9700938 A1	09/01/97	DE 19623623 A	02/01/97
		FR 2735786 A	27/12/96
		GB 2302548 A	22/01/97
		GB 9612409 D	00/00/00
		NL 1003384 A,C	00/00/00
WO 9610072 A1	04/04/96	AU 3584195 A	19/04/96
		CA 2199816 A	04/04/96
		EP 0784669 A	23/07/97
WO 9113139 A1	05/09/91	AU 660605 B	06/07/95
		AU 7344191 A	18/09/91
		CA 2036593 A	27/08/91
		DE 69112671 D,T	01/02/96
		EP 0444858 A,B	04/09/91
		ES 2078435 T	16/12/95
		JP 5503548 T	10/06/93
		US 5468418 A	21/11/95
WO 9209678 A1	11/06/92	AU 9028391 A	25/06/92
		CA 2096956 A	27/05/92
		EP 0559703 A	15/09/93
		JP 6502663 T	24/03/94
		NZ 240754 A	26/05/95

